



OFFICIAL LISTING

NSF certifies that the products appearing on this Listing conform to the requirements of
NSF/ANSI/CAN 61 - Drinking Water System Components - Health Effects

This is the Official Listing recorded on June 13, 2023.

Garlock Sealing Technologies
1666 Division Street
Palmyra, NY 14534
800-448-6688
315-597-3231



Facility: # 1 USA

Mechanical Devices

Trade Designation	Size	Water Contact Temp	Water Contact Material
Potable Water Materials [1] [G]			
98206	50 sq. in/L	C. HOT	EPDM

[1] Certified for use in distribution system valves as a material to encapsulate the disc.
The surface area to volume ratio may not exceed the ratio listed under size.

[G] Product is Certified to NSF/ANSI 372 and conforms with the lead content requirements
for "lead free" plumbing as defined by California, Vermont, Maryland, and Louisiana
state laws and the U.S. Safe Drinking Water Act.

Facility: Ciudad de México, Mexico

Joining and Sealing Materials

Trade Designation	Size	Water Contact Temp	Water Contact Material
Gasket/Sealing Materials [G]			
Garlock Multi-Swell™ (Style 3760-U)	[1]	CLD 23	OTHER

[1] Certified for a maximum width of 1/8" when used with pipes 1' - 144' in diameter.

[G] Product is Certified to NSF/ANSI 372 and conforms with the lead content requirements
for "lead free" plumbing as defined by California, Vermont, Maryland, and Louisiana
state laws and the U.S. Safe Drinking Water Act.

Facility: Palmyra, NY

Joining and Sealing Materials

Trade Designation	Size	Water Contact Temp	Water Contact Material
Gasket/Sealing Materials [G]			
97751	[1]	C. HOT	EPDM
Garlock Gylon Style 3522	[1]	CLD 23	PTFE

Note: Additions shall not be made to this document without prior evaluation and acceptance by NSF.



Garlock Gylon Style 3522 Stress Saver	[1]	CLD 23	PTFE
Garlock Multi-Swell™ (Style 3760-U) - Palmyra	[2]	CLD 23	OTHER
Stress Saver® XP	1/2" - 24"	C. HOT	FE
Style 3505 Blue Gylon® [3]	1" - 144"	CLD 23	PTFE
Style 3505 Blue Gylon® [3]	1" - 144"	CLD 23	PTFE
Stress Saver			
Style 3505 EPX Blue Gylon® [3]	1" - 144"	CLD 23	PTFE
Style 9780	1/2" - 24"	C. HOT	FE
O-Rings [G]			
97751	[1]	C. HOT	EPDM

- [1] Certified for a maximum surface area to volume ratio of 2.0 sq. in./L.
- [2] Certified for a maximum width of 1/8" when used with pipes 1" - 144" in diameter.
- [3] Certified for distribution systems only, with width exposures of no more than 1/2" in pipes with diameters shown in 'Size'.
- [G] Product is Certified to NSF/ANSI 372 and conforms with the lead content requirements for "lead free" plumbing as defined by California, Vermont, Maryland, and Louisiana state laws and the U.S. Safe Drinking Water Act.

Mechanical Devices

Trade Designation	Size	Water Contact Temp	Water Contact Material
Diaphragms [1]			
Garlock Gylon Style 3522 [G]	1" - 30"	CLD 23	PTFE
Garlock Gylon Style 3527 [G]	1" - 30"	CLD 23	PTFE

- [1] Certified for a maximum of 176 sq. in./L. in pumps and valves 1" in diameter and greater.
- [G] Product is Certified to NSF/ANSI 372 and conforms with the lead content requirements for "lead free" plumbing as defined by California, Vermont, Maryland, and Louisiana state laws and the U.S. Safe Drinking Water Act.

Facility: Houston, TX

Joining and Sealing Materials

Trade Designation	Size	Water Contact Temp	Water Contact Material
Gasket/Sealing Materials			
PSI Link Seal Modular Seal (LS-XXX-S61™-Y)	[1]	CLD 23	MLTPL

- [1] Certified for sealing the annular space between the outside of the pipe and the tank wall at a maximum use of 1 link per 5.8 gallons of water.

Note: Additions shall not be made to this document without prior evaluation and acceptance by NSF.